



Gasketing, Epoxys & Sealants

Gasketing Compounds

Red RTV Gasket 340

CRC Red RTV Gasket 340 is formulated for heavy duty, high temperature applications with an intermittent service temperature of up to 340°C. CRC Red RTV Gasket 340 is a self-forming room temperature vulcanising silicone that replaces almost any cut gasket, felt, cork, paper, asbestos and rubber gaskets. No gasket sealers are required – the pure silicone rubber forms to any size and shape quickly.

Features

- Intermittent service temperature of up to 340°C
- Makes any size or shape of gasket in minutes
- Ideal for high temperature, high pressure applications
- Replaces most gaskets
- Remains flexible and durable
- Easy to apply

Code	Size
8629	Tube (Blister Pack 85gm)
5078	Cartridge 300gm



Grey RTV Gasket Sensor Safe

CRC Grey Gasket is formulated for high torque applications. The non-acidic RTV silicone gasket is safe for use around sensors. It is odourless, non-corrosive and has excellent oil resistance. CRC Grey RTV Gasket is ideal to replace almost any cut gasket, felt, cork, paper, asbestos and rubber gaskets. No gasket sealers are required.

Features

- Continuous service temperature of 250°C, intermittent service temperature of up to 330°C
- Resists migrating caused by thermal cycles, cracking, shrinking and vibration
- Highly resistant to auto and industrial fluids
- The pure silicone rubber forms to any size and shape quickly
- Remains flexible and durable

Code	Size
8637	Tube (Blister Pack 85gm)
5079	Cartridge 300gm



Red Gasket 260

ADOS Red Gasket 260 is formulated for heavy duty, high temperature applications with a continuous service temperature of up to 260°C. ADOS Red Gasket 260 is a self-forming room temperature vulcanising silicone that replaces felt, cork, paper, asbestos and rubber gaskets. No gasket sealers are required – the pure silicone rubber forms to any size and shape quickly. ADOS Red Gasket 260 resists migrating caused by thermal cycles, cracking, shrinking and vibration. It is ideal for high temperature, high pressure applications, it will remain flexible and durable. ADOS Red Gasket 260 is NOT recommended for use on copper and brass. Do not use as a head gasket, not suitable for stove pipes or in fireplaces.

Features

- Continuous service temperature of up to 260°C
- Makes any size or shape of gasket in minutes
- Ideal for high pressure, high temperature applications
- Suitable for general machinery and automotive gaskets
- Resists cracking, shrinking and vibration
- Easy to apply

Code	Size
8380	Cartridge 300gm



Maniseal Exhaust Cement

CRC Maniseal BROWN Exhaust Cement is a sealing and gasketing compound designed exclusively for use in assembly of Automotive Exhaust Systems. It expands and sets when heated, ensuring a perfect seal against carbon monoxide and other noxious fumes. CRC Maniseal BLACK Exhaust Cement is a sealing and gasketing compound designed to seal joints in fire boxes and flues or for repairing kilns. It expands and sets when heated, ensuring a perfect seal against carbon monoxide and other noxious fumes. Can be used for an exhaust system when black is the desired colour.

Features

- Cleans up in water
- Withstands very high temperatures
- Bridges gaps and imperfections in exhaust clamping areas

Code	Size
5061	Tube 145g (Brown)
5063	Cartridge 575g (Brown)
5064	Tube 145g (Black)
5066	Cartridge 575g (Black)



The Professional's Choice

www.crc.co.nz

Silicones & Sealants Contractors Range



Universal Silicone Sealant

ADOS Universal Silicone is a weather resistant sealant that is translucent allowing it to blend into its surrounding surfaces. The mould and mildew resistant properties make the sealant ideal for kitchen, bathroom and other plumbing applications.

Features

- 100% Silicone
- Waterproof sealant
- Mould and mildew resistant
- Indoor and outdoor use
- Low odour
- UV Resistant
- Flexible
- Translucent

Code	Size
8358	Cartridge 310ml



RTV Acetic Cure Silicone Sealant

ADOS RTV Acetic Cure Silicone is a single component, fast curing, room temperature vulcanising silicone designed for glazing applications, general sealing and weatherproofing.

Features

- 100% RTV silicone
- Acetic cure for extra bond and increased strength
- Permanently flexible
- Waterproof sealant
- Excellent adhesion
- Ideal for glazing
- UV resistant
- Withstands NZ conditions.
- Translucent

Code	Size
8365	Cartridge 310ml



RTV Neutral Cure Silicone Sealant

ADOS RTV Neutral Cure Silicone is a single component general purpose, fast curing, room temperature vulcanising silicone. Specially formulated and translucent in colour for use with most materials such as ceramics, steel, aluminium, concrete, brick, glass, most painted surfaces and most plastics to form a flexible weather-proof seal.

Features

- 100% RTV silicone
- Neutral cure, non-corrosive
- Permanently flexible
- Waterproof sealant
- Excellent adhesion
- Withstands NZ conditions
- Translucent

Code	Size
8360	Cartridge 310ml



Roof & Plumbing Silicone Sealant

ADOS Roof and Plumbing Silicone is specially formulated and translucent in colour for use with zinc coated/galvanised metal products, aluminium frames and fiberglass to glaze, seal and waterproof.

Features

- 100% silicone
- Permanently flexible
- UV resistant
- Neutral cure, non-corrosive
- Waterproof sealant
- Excellent adhesion
- Withstands NZ conditions
- Translucent

Code	Size
8359	Cartridge 310ml



Nail-It Panel Adhesive

ADOS Nail It is a flexible, waterproof adhesive designed for bonding gypsum, timber paneling and shower linings to wood or metal studs, concrete or block walls.

ADOS Nail It will cure to a tough, rubbery bead with excellent permanent adhesion. Nail it eliminates nail pops and squeaks in flooring. It also bridges minor framing gaps and reduces sound transmission.

Features

- No Slump
- Excellent wet grab
- High bond strength
- Waterproof
- Tough and flexible

Code	Size
8318	Cartridge 345g



Galvseal Adhesive Sealant

ADOS Galvseal is a versatile, high solids adhesive sealant with high performing gap-filling qualities. It gives excellent adhesion to many materials and bonds metal to wood, ceramic tiles, metal, stone, concrete, powder coating, aluminium and some plastics. Galvseal has outstanding abrasion and heat resistance, is waterproof and resistant to grease, oil and most solvents.

Features

- Non-elastic, rigid sealant.
- Oil and solvent resistant.
- Abrasion resistant
- Rapid drying
- Waterproof sealant
- Withstands harsh temperatures
- For interior and exterior use
- Grey colour

Code	Size
8337	Cartridge 310ml



Silicones & Sealants



MS High Performance Adhesive Sealant

ADOS MS Sealant is a high performance, one-component neutral curing adhesive sealant based on MS Polymers. It has excellent primerless adhesion to all materials commonly used in the demanding building, construction and engineering industries. It is ideal where silicone sealants are not suitable.

ADOS MS Sealant is formulated for durable bonding, sealing and waterproofing gaps in dilation joints. This innovative product cures quickly in ambient temperatures and retains excellent bond strength, elasticity and tear resistance over the years. It skins over in a short time resisting dust and dirt pickup and can be applied in thick layers without shrinking or bubbling.

Features

- Excellent adhesion strength
- Waterproofs, bonds and seals
- Paintable
- Extreme flexibility
- Will not crack
- Interior and exterior use
- Low VOC, low odour
- UV resistant

Code	Size
8361	Cartridge White 400g
8362	Cartridge Clear 300g
8363	Cartridge Black 400g
8364	Cartridge Grey 400g

	ABS Plastic	Acrylic Plastic	Aluminium	Brass	Brick	Carpet	Ceramics	Copper	Cork	Fiberglass-wool	Fiberglass-sheet	Fibrolite	Glass	Gib board	Lead	Marbalex	Masonry	Metal	Particleboard	Perspex	Polystyrene sheet	Timber
Ados Universal	✓	✓	✓	✓	✓		✓	✓			✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓
Ados Roof & Plumbing	✓	✓	✓	✓	✓		✓	✓			✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓
Ados RTV Neutral Cure	✓	✓	✓	✓	✓		✓	✓			✓	✓	✓		✓	✓	✓	✓	✓	✓	✓	✓
Ados RTV Acetic Cure	✓	✓			✓		✓				✓	✓	✓		✓	✓			✓	✓	✓	✓
Ados Galvseal	✓	✓	✓	✓	✓		✓	✓			✓	✓			✓	✓	✓	✓		✓		
Ados Nail-IT			✓	✓	✓		✓	✓	✓	✓	✓	✓		✓			✓	✓	✓	✓		✓
Ados MS Sealant	✓	✓	✓	✓	✓		✓	✓	✓		✓	✓		✓	✓	✓	✓	✓	✓	✓	✓	✓

The Professional's Choice

www.crc.co.nz

Epoxy Mortar

Resamax Epoxy Mortar



ADOS Epoxy Mortar is a two part silica based epoxy. Once mixed, the putty can be easily moulded to form permanent watertight repairs with a smooth finish to concrete, brick, mortar and plaster. It adheres well to wet surfaces and is suitable for most underwater repairs. In cured form ADOS Epoxy Mortar is many times harder and more impact resistant than concrete, has a similar consistency and colour to new concrete, and has excellent chemical and UV resistance.

Features

- Cures harder than concrete
- Suitable for repairs to submerged substrates
- Adheres to wet surfaces
- Excellent cohesive properties in uncured state

Code	Size
4503	Pack 1 Litre
4505	Pack 2 Litre
4506	Pack 8 Litre
4550	Resin Pail 10 Litre
4555	Hardener Pail 10 Litre



Epoxy Putty

CRC Minute Mend Epoxy Putty



Minute Mend is a versatile epoxy putty packaged in a convenient one piece stick for immediate, permanent repairs. It can be used to reshape, rebuild or permanently repair a variety of surfaces and applications. It is hand-kneadable and mixes in just one minute. Minute Mend is ideal to permanently repair scratches, gouges and holes, to perform routine electrical jobs and to stop leaks. It can be used for plumbing, electrical, ceramic, vehicle and machinery repair. Once fully cured Minute Mend can be sanded, filed, tapped, sawed, drilled, machined, stained or painted. It also bonds to both wet and dry surfaces.

Features

- Convenient easy, no mess and is ready to use in less than one minute
- Ideal to reshape, rebuild, or permanently repair a variety of surfaces and applications
- Cures steel hard
- Will not sag, run or drip

Code	Size
14070	Tube 4oz

Timber Sealer/Primer

ADOS Timber Sealer/Primer



ADOS Timber Sealer/Primer is an equal mix epoxy coating. Once applied it soaks deep into the timber cells and hardens to an extremely tough epoxy coat. This effectively densifies the timber. The dense coat stops any water entering staining or rotting the timber. ADOS Timber Sealer/Primer can be painted over with varnishes, oil paints and acrylic paints. It is an ideal sealer for new timber. ADOS Timber Sealer/Primer also kills existing bacteria which cause rotting in timber.

Features

- Excellent long term microbiocidal barrier coating for all marine and general situations
- An unfilled low viscosity resin and hardener of clear honey colour, which is supplied in a handy 1:1 mixing ratio form

Code	Size
4360	Resin 4 Litre
4365	Hardener 4 Litre



Epoxy Resin



All Purpose Resin

A superior purpose designed laminating/sheathing and adhesive system. Designed for extreme durability in marine and general applications.

ADOS All Purpose Resin's low mixed viscosity ensures good penetration and provides superior wet out and cured characteristics at ambient temperatures. It is especially suited for use with fibreglass cloth in the surface protection of timber in marine situations. No thinning required.

Features

- With fibreglass cloth as the moisture barrier on wooden boat hulls
- Use "neat" as an osmosis barrier coating on most boat hulls
- In automotive repairs
- Building and decking projects
- Can be used in conjunction with glass matting

Code	Size
4104	Pack 625ml
4106	Pack 1.25 Litre
4140	Pack 5 Litre
4150	Resin Jerry Can 16 Litre
4155	Hardener Fast Pail 4 Litre
4156	Hardener Slow Pail 4 Litre
4170	Resin Drum 200 Litre
4175	Hardener Fast Jerry Can 10 Litre
4176	Hardener Slow Jerry Can 10 Litre

Rapid Set Resin



Ados Rapid Set Resin is a high-performance two part epoxy glue. Its high speed cure makes it ideal for fast permanent repairs to almost anything. The one to one mix eliminates wastage and guarantees performance.

Ideal for jobs where finished appearance is important. Can also be varnished and painted. Will not swell on prolonged immersion in water.

Features

- Sets in 5 minutes
- Designed to repair cracks and dents
- An excellent epoxy for jobs where speed of cure is essential
- Can be used in conjunction with glass matting

Code	Size
4463	Pack 250ml

