


NZ POISONS CENTRE 0800 764 766 | NZ EMERGENCY SERVICES: 111 - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

CRC (NZ) 5-56 industrial Bulk

INGREDIENTS	CAS NO	%	TWA
naphtha petroleum, heavy, hydrotreated	64742-48-9.	50-70	5 mg/m3
mineral oil	63748-98-1	20-40	5 mg/m3

GHS	DG
	UN No: Not Applicable Hazchem Code: Not Applicable DG Class: Not Applicable Subsidiary Hazard: Not Applicable Packing Group: Not Applicable

PROPERTIES



Liquid. Does not mix with water. Floats on water. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). Seek medical advice. Do NOT give milk or oil. Do NOT give alcohol.
Eye:	Wash with running water.
Skin:	Remove contaminated clothing. Wash with soap & water.
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Emesis generally unnecessary. Debride for subcutaneous injection. Evaluate for respiratory distress. Consider lavage with cuffed tube. NO adrenalin.
Fire Fighting:	Foam.
Spills and Disposal:	Eliminate ignition sources. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together

o — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

HEALTH HAZARD INFORMATION



Determined by Chemwatch using GHS/HSNO criteria Gazetted by EPA New Zealand	3.1D, 6.1E (aspiration), 6.4A, 9.1C
Signal word:	Danger
Hazard statement(s):	H227 Combustible liquid. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H412 Harmful to aquatic life with long lasting effects.

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Consider chemical goggles.
Gloves:	PVC chemical resistant type.
Respirator:	Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Keep out of reach of children. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

Chemwatch: 23-4518
 Print Date: 10/04/2026
 Initial Date: Not Available
 Revision Date: 27/10/2023