



NZ POISONS CENTRE 0800 764 766 | NZ EMERGENCY SERVICES: 111 - THIS IS A SUMMARY ONLY - FULL REPORT AVAILABLE

## 121 Fibreglass Epoxy Repair System Part B

INGREDIENTS	CAS NO	%	TWA
p-tert-butylphenol	98-54-4	<10	3 mg/m3
benzyl alcohol	100-51-6	10-30	-
isophorone diamine	2855-13-2	10-30	-
formaldehyde/ phenol/ triethylenetetramine copolymer	32610-77-8	<10	-

GHS	DG
	 <p>UN No: <b>2735</b>            Hazchem Code: <b>2X</b>            DG Class: <b>8</b>            Subsidiary Hazard: <b>Not Applicable</b>            Packing Group: <b>III</b></p>

### PROPERTIES



Liquid. Does not mix with water. Corrosive. Alkaline. Combustible.

### EMERGENCY



### FIRST AID

<b>Swallowed:</b>	Give water (if conscious). URGENT MEDICAL ATTENTION.
<b>Eye:</b>	Wash with running water (minimum 15 mins). Medical attention.
<b>Skin:</b>	Flood body with water. Remove contaminated clothing. Wash with water.
<b>Inhaled:</b>	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
<b>Advice To Doctor:</b>	Irrigate eyes with saline. Supportive care.
<b>Fire Fighting:</b>	Water spray/ fog.
<b>Spills and Disposal:</b>	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

### HEALTH HAZARD INFORMATION



<b>Determined by Chemwatch using GHS/HSNO criteria Gazetted by EPA New Zealand</b>	8.1A, 6.1D (oral), 8.2A, 8.3A, 6.5A (respiratory), 6.5B (contact), 6.8A, 9.1C
<b>Signal word:</b>	<b>Danger</b>
<b>Hazard statement(s):</b>	<p><b>H290</b> May be corrosive to metals.</p> <p><b>H302</b> Harmful if swallowed.</p> <p><b>H314</b> Causes severe skin burns and eye damage.</p> <p><b>H317</b> May cause an allergic skin reaction.</p> <p><b>H334</b> May cause allergy or asthma symptoms or breathing difficulties if inhaled.</p> <p><b>H360</b> May damage fertility or the unborn child.</p> <p><b>H412</b> Harmful to aquatic life with long lasting effects.</p>

### SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



**x** — Must not be stored together  
**0** — May be stored together with specific preventions  
**+** — May be stored together

*Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.*

### PRECAUTIONS FOR USE



<b>Appropriate engineering controls:</b>	General Exhaust Ventilation adequate.
<b>Glasses:</b>	Consider full face-shield.
<b>Gloves:</b>	1.BUTYL 2.VITON
<b>Respirator:</b>	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
<b>Storage and Transportation:</b>	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.
<b>Fire/Explosion Hazard:</b>	Toxic smoke/fumes in a fire. Attacks metals to liberate hydrogen.

Chemwatch: 5295-85  
 Print Date: 10/04/2026  
 Initial Date: Not Available  
 Revision Date: 05/06/2024