

Epoxy Glue Hardener (Part B)

INGREDIENTS	CAS NO	%	TWA
phenol	108-95-2	1-2	3.8 mg/m3
tall oil/ tetraethylenepentamine polyamides	68513-05-3	30-50	-
benzyl alcohol	100-51-6	5-10	-
formaldehyde/ phenol/ triethylenetetramine copolymer	32610-77-8	1-5	-

GHS	DG
	UN No: 2735 Hazchem Code: 2X DG Class: 8 Subsidiary Hazard: Not Applicable Packing Group: III

HEALTH HAZARD INFORMATION

Determined by Chemwatch using GHS/HSNO criteria Gazetted by EPA New Zealand	8.1A, 6.1D (oral), 8.2C, 8.3A, 6.5B (contact), 6.8A, 6.9B, 9.1A
Signal word:	Danger
Hazard statement(s):	H290 May be corrosive to metals.
	H302 Harmful if swallowed.
	H314 Causes severe skin burns and eye damage.
	H317 May cause an allergic skin reaction.
	H360 May damage fertility or the unborn child.
	H373 May cause damage to organs through prolonged or repeated exposure.
	H410 Very toxic to aquatic life with long lasting effects.

PRECAUTIONS FOR USE



Appropriate engineering controls:	General Exhaust Ventilation adequate.
Glasses:	Safety Glasses. Consider full face-shield.
Gloves:	1.BUTYL 2.VITON 3.TEFLON 4.PVA
Respirator:	Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)
Storage and Transportation:	Store in cool, dry, protected area. Restrictions on Storage apply. Refer to Full Report. Keep locked up. Keep out of reach of children. Keep away from living quarters. Keep away from food, drink and animal feeding stuffs.
Fire/Explosion Hazard:	Toxic smoke/fumes in a fire.

PROPERTIES



Liquid. Does not mix with water. Corrosive. Alkaline. Combustible.

EMERGENCY



FIRST AID

Swallowed:	Give water (if conscious). URGENT MEDICAL ATTENTION.
Eye:	Wash with running water (minimum 15 mins). Medical attention.
Skin:	Flood body with water. Remove contaminated clothing. Wash with water
Inhaled:	Fresh air. Rest, keep warm. If breathing shallow, give oxygen. Medical attention.
Advice To Doctor:	Treat symptomatically. Irrigate eyes with saline. Supportive care.
Fire Fighting:	Water spray/ fog. Foam - alcohol type.
Spills and Disposal:	Eliminate ignition sources. Prevent from entering drains. Contain spillage by any means. Absorb with dry agent. Stop leak if safe to do so. This material and its container must be disposed of in a safe way. To clean the floor and all objects contaminated by this material, use water and detergent.

SAFE STORAGE WITH OTHER CLASSIFIED CHEMICALS



x — Must not be stored together

o — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.