TECHNICAL DATA SHEET

CRC RE-PO Cutting Compound



CRC RE-PO Cutting Compound is designed to remove heavily weathered layers of paintwork and rejuvenate poor surfaces. It also removes imperfections, old waxes, tar and scratches. After using CRC RE-PO Cutting Compound, surfaces should be polished with CRC RE-PO Cream Polish.

CRC RE-PO Cutting Compound contains a high quality, specially selected abrasive that is ideally suited for hand rubbing applications.

Not recommended for paintwork in good condition, or on newer cars with metallic paint.

Item Code: 9500 **Pack Size: 300g Tin**

Features and Benefits

- **High cut strength:** Quickly & easily cuts through oxidized surfaces.
- **Easy application:** Suitable for machine or hand rubbing applications.
- **Removes imperfections, old waxes, tar, scratches, swirl marks, stains & paint defects**.
- **Rejuvenates heavily weathered, dull & faded surfaces.**

Applications

Suitable for use on automotive paintwork. Ideal for removing heavily weathered layers of paintwork and for restoring poor surfaces.
Not recommended for paintwork in good condition, or on newer cars with metallic paint.

Typical Properties and Characteristics

Flash Point	44°C
Boiling Point	150 - 200°C
Odour	Mild odour
Appearance	Coloured viscous liquid
Solubility	Immiscible in water

% Volatile	N/A
Vapour Density	>1
Specific Gravity	1.2
Flammability	Flammable

TECHNICAL DATA SHEET

CRC RE-PO Cutting Compound

Directions

1. Wash vehicle and chamois dry.
2. Make a pad of clean, open weave cloth or use sponge supplied.
3. Apply CRC RE-PO Cutting Compound to the pad. NEVER DIRECTLY ONTO THE JOB.
4. Use sparingly, as too much hinders the cutting action.
5. Apply over a small area. Rub with straight back and forth motion until the desired surface is obtained, then finish with another clean, dry cloth.
6. If thinning is required, add water and stir until the desired consistency is obtained.
7. Protect and preserve the finish with CRC RE-PO Cream Polish.

HANDY HINTS:

1. Do not apply on hot surfaces or in direct sunlight.
2. Do not use on non-painted surfaces or plastic trim.

NOTE: Keep tin airtight.

NOT RECOMMENDED FOR PAINTWORK IN GOOD CONDITION, OR ON NEWER CARS WITH METALLIC PAINT.

Special Precautions

General:
Flammable liquid and vapour. Causes skin and serious eye irritation. Harmful if inhaled. May cause drowsiness or dizziness. May cause damage to organs through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe vapours. Use only outdoors or in a well-ventilated area. Take action to prevent static discharges. Store in a well-ventilated place. Keep cool. Store locked up. Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

Refer to **Safety Data Sheet** for more details.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

Contact Information

CRC Industries NZ
10 Highbrook Drive, East Tamaki
Auckland, New Zealand

www.crc.co.nz
PH: 09 272 2700
Email: info.nz@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries NZ makes no representations or warranties of any kind concerning this data.

Technical Data Sheet *Version 07/2026*