



CRC ADOS Food Grade Sealant is a low modulus silicone joint sealant with 100% neutral cure. This highly flexible sealant contains additives to resist mould and mildew, with excellent adhesion to plastics, ceramics, stainless steel, metals and glass. The chemically stable formulations show little change in physical properties after exposure to moisture and temperature extremes.

It is specially formulated for use in food, pharmaceutical and other clean environments where MPI certification is required, ideal for refrigerated rooms or household and other commercial uses.

Item Code: 3312

Pack Size: 300g Cartridge

Features and Benefits

- **Highly flexible with excellent adhesion**
- **Works on wet & dry surfaces**
- **Mould & mildew resistant**
- **Waterproof seal**
- **MPI Approved C82** for all animal product except dairy
- **MPI Approved** for use at farm dairies and in dairy processing

Typical Properties and Characteristics

Composition	Silicone polymer
Curing Method	Neutral (Oxime)
Colour	Translucent
Service Temperatures	-60°C to +150°C
Hardness (Shore A)	20-35
Slump	< 1mm

Tensile Strength	> 1.0 Mpa
Dynamic Joint Movement	± 25%
Density	1.04
Tooling Time	6-20 minutes
Tack Free Time	20 minutes
Cure Time (5mm, 20°C 55% RH)	2 days

Estimating Requirements: Linear metres per cartridge for various joint dimensions

Depth mm	Width mm						
	3.3	6.4	9.7	12.7	16.0	19.2	25.4
3.3	29.7	14.88	9.93	7.44	5.94	4.97	3.72
4.9		9.93	6.64	4.97	3.96	3.31	2.48
6.4		7.42	4.97	3.72	2.97	2.49	1.86
9.7			3.31	2.48	1.98	1.64	1.23

Directions

1. Surface must be clean and dry before application.
2. Use mechanical or solvent cleaning. Do not use soap or detergent.
3. Use masking tape to cover surfaces and joints to simplify cleaning.
4. If surface requires primer, the primer must be dry before applying sealant.
5. Before placing cartridge in application gun, slice nozzle at 45 degree angle at desired bead size.
6. Press nozzle against surface and apply sealant.
7. Tool to eliminate all voids within 5 minutes of applying sealant. Tack-free time is 1 hour.
8. Sealant will fully cure in 72 hours.
9. Remove masking tape within 1 hour. Any uncured sealant can be cleaned up with mineral turpentine.

Wet Materials:

1. Remove surface water as much as possible.
2. Keep nozzle close to surface so extruding sealant immediately contacts the surface.
3. Tool the sealant immediately into joint
4. Adhesion will improve on drying. Where adhesion is difficult, wipe the surface with solvent and apply sealant to partially dry substrate.
5. Food Grade Sealant will seal on non-porous surfaces such as glass, metal and tiles, but adhesion to porous substances such as cement and timber may not be possible while wet.

Special Precautions

General:

Uncured sealant may cause skin, eye and respiratory system irritation. Use only in well ventilated areas. Use appropriate personal protection to avoid contact with skin and eyes.

Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 2 years from the date of manufacture.

Contact Information

CRC Industries NZ
10 Highbrook Dr, East Tamaki
Auckland, New Zealand

www.crc.co.nz
PH: 09 272 2700
Email: info.nz@crcind.com

Disclaimer: All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries NZ makes no representations or warranties of any kind concerning this data.

Technical Data Sheet Version 10/2024