



Plumbing and Drainage Focus

ADOS

F2 Contact Adhesive

ADOS F2 is a high performance general purpose contact adhesive. It is water resistant and flexible and its high bond strength makes it ideal for a wide range of uses. ADOS F2 is easily applied, highly versatile, durable and bonds instantly to most substrates.



Size	75ml Tube	75ml Blister Tube	125ml	250ml
Code	8002	8003	8006	8008

Size	500ml	1 Litre	2 Litre	4 Litre	20 Litre
Code	8009	8010	8012	8014	8016



CDT Cutting Oil



A cutting, drilling and thread cutting lubricant formulated for hand and machine cutting on all types of metal. Reduces friction and wear, improves surface finish and increases tool life. Contains extreme pressure additives and creates a strong film with increased 'cling' for use on vertical surfaces. Leaves an anti-corrosive residue and is safe to use on soft metals such as brass, copper and aluminium.

Type	Aerosol	Paste
Size	400ml	250ml
Code	3063	3061



Leak Stop - even under water



An instant waterproofing sealant that can be applied in rain, snow, and even under water, sealing immediately with no fear of wash off. Bridges cracks and gaps up to 10mm in both WET and DRY conditions. Provides superior flexibility, strength, and durability, perfect for almost every application. It can be applied in extreme temperatures from -5°C to 40°C without the need for primer, and maintains temperature resistance from -25°C to 100°C.

Colour	Clear	Grey
Size	300ml	300ml
Code	8492	8490

ADOS

UHS Aerosol Adhesive



An ultra high strength contact adhesive which gives an immediate and permanent bond on a wide variety of surfaces. It is formulated to give low soak, cure fast, dry clear and be non-staining. It has high heat resistance and is suitable on porous and non-porous surfaces. Ideal for applications where permanent high strength bonds are essential. Variable spray width and no clamping required.

Size	550ml
Code	8180



Exoff Degreaser & Parts Cleaner



Biodegradable, non-toxic, non-hazardous, non-flammable, pH neutral, and water soluble. Powerful yet non-abrasive, non-corrosive, and contains no solvents. Penetrates grease and grime, wax, silicone, cutting and tapping oils and many other contaminants quickly and effectively. Use confidently on all metals and alloys – will not damage bright metals including aluminium and brass. Safe on fibreglass, glass, plastics, rubber, painted surfaces and laminates.

Size	750ml	5 Litre
Code	3410	3412



ADOS

www.crc.co.nz



Rust Converter



A unique fast drying coating formulated for treatment of lightly rusted or correctly prepared metal surfaces that neutralises rust and converts it to a tough black primer. It binds to the surface and provides a waterproof barrier for effective long-lasting rust protection. Can be used as a finish coat or be painted over. To promote a high quality topcoat finish, apply CRC Prep It as an intermediate primer over CRC Rust Converter prior to top coating.

Size	250ml	1 Litre	5 Litre
Code	3073	18418	3075



Silicone Grease



A thin non-curing silicone grease designed for sealing, lubricating and waterproofing o-rings and other rubber and plastic parts. It insulates valves, fasteners, electrical contacts, spark plugs and battery terminals from moisture and protects against corrosion. Resistant to oil, water and chemicals and with a temperature range of -40°C to +200°C it will not harden, freeze, dry or melt. Safe on most rubber and plastics. Chemical, oil and water resistant.

Size	75ml
Code	3036



Zinc It



A quick drying coating that offers the same advantages as hot-dip galvanising. Forms a highly-protective coating with 95% highest purity zinc on bare steel or iron surfaces. Reapplication period up to 6 years.

Size	350gm	1 Litre
Code	2085	2185



Bright Zinc



Combines superior rust inhibiting properties of zinc with a tough but flexible enamel coating and the bright finish of new galvanising. More than 50% highest purity zinc in the dried film.

Size	400ml	1 Litre
Code	2087	2187



Black Zinc



A quick drying coating that combines superior rust inhibiting properties of zinc with a tough but flexible enamel coating and a coloured satin finish. High levels of anti-corrosive zinc complexes.

Size	400ml	1 Litre
Code	2089	2189



Air Brush



Supplies a powerful burst of compressed pure propellant gas to safely remove dust and lint from all delicate precision equipment and hard-to-reach areas. Versatile and handy and should be part of every servicing kit – ideal for off-site servicing when compressed air is not available. Non-abrasive, non-corrosive, moisture-free, leaves no residue. Safe on all plastics. Non-flammable.

Size	300g
Code	2066



Leak Detector



Formulated for the quick and easy site detection of gas and air leaks. The water-based formula contains no oils, silicones or harmful solvents. Quickly and reliably locates gas leaks and pressure losses in pipes and pressurised systems by forming highly visible bubbles when applied over any leak. No odour and non-flammable.

Size	510g
Code	14503



Solvent N



A general purpose cleaner used for cleaning equipment, brushes, rollers etc contaminated with neoprene adhesives, for pre-wiping surfaces prior to applying adhesives and can soften dried flooring adhesives to assist with easier removal. Can be added sparingly to adhesives as a thinner.

Size	500ml	1 Litre
Code	8200	8202



F38 Heat Resistant Contact Adhesive



An outstanding heat resistant contact adhesive capable of withstanding temperatures of up to 175°C. Especially suited to areas where very high heat is encountered and where surfaces are exposed to direct sunlight. Has a short tack time and the instant bond necessitates small areas to be worked at any time. May be applied using a brush, roller, air driven sprayer or airless spray equipment.

Size	500ml
Code	8034



ADOS

Resamax Epoxy Mortar



A two part silica based epoxy. Once mixed, the putty can be easily moulded to form permanent watertight repairs with a smooth finish to concrete, brick, mortar and plaster. It adheres well to wet surfaces and is suitable for most underwater repairs. In cured form Ados Resamax Epoxy Mortar is many times harder and more impact resistant than concrete, has a similar consistency and colour to new concrete, and has excellent chemical and UV resistance.

Size	1 Litre	2 Litre	8 Litre	10 Litre Resin	10 Litre Hardener
Code	4503	4505	4506	4550	4555



5.56



A multi-purpose service spray that lubricates moving parts for smooth action, breaks through rust and corrosion, displaces water from wet equipment and protects metals from corrosion. Eliminates the need for many disassembly operations and cleans grease and tar off painted surfaces. Safe on all metals and alloys and on most painted surfaces, coatings, plastics and rubbers.

Size	70ml	200ml	400ml	20 Litre
Code	5002	5028	5005	5006



808 Silicone Spray



A multi-purpose silicone spray for general lubrication. Leaves a thin, clear, non-staining, odourless film that revives, waterproofs and lubricates. Provides ongoing protection and is ideal for use on metals, plastics, rubbers, fabrics, wood, glass and painted surfaces. Excellent mould release, parting agent and machine bed lubricant. Wide Temperature Range from -38°C to +290°C.

Size	500ml
Code	3055

ADOS

Multipurpose Spray Adhesive



Bonds most materials quickly and easily, giving a long lasting bond. It is formulated to give a fast tack off, low soak spray and dries clear. Repositionable for 1-2 minutes eliminating costly errors with expensive materials. Once positioned, the adhesive will bond within 10-20 minutes. Full cure will take 24 hours.

Size	210ml	575ml
Code	8015	8017



Pipe Thread Sealant



Non-toxic, non-drying thread sealing compound complete with convenient brush top. Engineered to produce a leak-proof seal between pipe thread connections (male and female). Has ability to hold pressures of up to 8000 PSI (55,158kPa). Temperature range -37°C to +287°C. Does not contain lead, graphite, molybdenum disulfide, or clay fillers.

Size	227g
Code	35401



Brakleen



Quickly and safely removes grease, oil, brake fluid and other contaminants from equipment, and mechanical components, without the need for disassembly. Fast evaporation minimises downtime. Non-staining, non-corrosive, leaves no residue and evaporates quickly.

Type	Original	Non Chlorinated
Size	600g	525ml
Code	5089	5084



Peel Off Label Remover



Uses the natural power of d-Limonene to soak through paper labels and release adhesive backings. Once released, the label can be easily removed from most containers and surfaces. Any residue can be easily removed with a wet cloth. Can also be used to effectively clean off cured adhesive and to remove industrial ink from machinery.

Size	400ml
Code	3352

**ADOS**www.crc.co.nz



MS Adhesive Sealant



Ados MS is a BRANZ APPRAISED high performance neutral cure adhesive sealant based on MS Polymers. Seals gaps in expansion joints in plumbing, roofing, concrete and brick. Exhibits extreme low shrinkage and is non-slump. Cures quickly, retains excellent bond strength, elasticity and tear resistance. The cured product can be painted with most solvent and water based paints.

Colour	Clear*	White	Black	Grey
Size	300g	400g	400g	400g
Code	8362	8361	8363	8364

*BRANZ Appraised except Clear.



121 Repair Anything



The revolutionary new way to make repairs. ADOS 121 is an epoxy polymer with glass fibres already integrated into the hardener – making use so easy. Easy 1:1 mixing, strong and flexible, bridges gaps, waterproof and can even be applied in the wet to almost any surface including polystyrene. Ideal for joining dissimilar objects eg metal to plastic.

Size	500ml
Code	4420



Roof & Plumbing Silicone Sealant



Fast curing room temperature vulcanizing silicone. Specially formulated and translucent in colour for use with zinc coated/galvanized metal products, aluminium frames and fiberglass to glaze, seal and waterproof. Also suitable for glass, ceramics, brick and most painted surfaces. Neutral cure, non-corrosive and UV resistant.

Size	310ml
Code	8359



Kitchen & Bath Silicone Sealant



Fast curing room temperature vulcanizing silicone. Specially formulated for wet areas inside the home or business. Contains an additive to fight mould and mildew. Excellent adhesion to glass, aluminium, ceramics, kitchen and bath fixtures, porcelain, showers, sinks and tiles. Cures white

Size	310ml
Code	8310



Maniseal



A sodium silicate based sealing and gasketing compound for use in fire boxes, flues, repairing kilns and for automotive exhaust systems. It expands and sets when heated, ensuring a perfect seal against noxious fumes. High temperature resistance up to 300°C. Cleans up in water.

Colour	Black		Brown	
Size	145g	530g	145g	530g
Code	5064	5066	5061	5063



Galvseal Adhesive Sealant



For use in plumbing, roofing, building, aluminium windows manufacturing applications both interior and exterior, metal and fabrication repairs and duct work. Dries very quickly to a hard, non-flexible, rigid film. Solvent based and can be painted over. Bonds metal to wood, ceramic tiles, metal, stone, concrete, powder coating, aluminium and some plastics. Outstanding abrasion and heat resistance, is waterproof and resistant to grease, oil and most solvents.

Size	310ml
Code	8337

