



# GREENLIGHT™

## FOOD SAFETY PROGRAM

ASSISTS AUDIT COMPLIANCE

# FOOD GRADE WHITE GREASE

PRODUCT CODE: 3038



### This document contains:

- SDS
- TDS
- MPI Approvals
- Allergen Certificate
- NSF Certificate

### MPI Approved

For use at Farm Dairies and in Dairy processing



### MPI Approved C15

All Animal Product Except Dairy



NSF

H1

Scan for  
Product  
Compliance



**Disclaimer:** Safety Data Sheet (SDS) is valid for 5 years only from the date of issue. MPI certification is also valid for 5 years from date of issue. Please scan QR code to validate this product's latest documents.



TOGETHER, WE GET IT DONE.™

[www.crc.co.nz](http://www.crc.co.nz)



# CRC Food Grade White Grease (Fg03038)

## CRC Industries (CRC Industries New Zealand)

Chemwatch Hazard Alert Code: 3

Chemwatch: 4731-04

Version No: 7.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Issue Date: 10/12/2021

Print Date: 02/10/2024

L.GHS.NZL.EN.E

### SECTION 1 Identification of the substance / mixture and of the company / undertaking

#### Product Identifier

Product name	CRC Food Grade White Grease (Fg03038)
Chemical Name	Not Applicable
Synonyms	Not Available
Proper shipping name	AEROSOLS
Chemical formula	Not Applicable
Other means of identification	Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Grease, lubricant-aerosol.
--------------------------	----------------------------

#### Details of the manufacturer or supplier of the safety data sheet

Registered company name	CRC Industries (CRC Industries New Zealand)
Address	10 Highbrook Drive East Tamaki Auckland New Zealand
Telephone	+64 9 272 2700
Fax	+64 9 274 9696
Website	<a href="http://www.crc.co.nz">www.crc.co.nz</a>
Email	- No EMAL ID NEEDED for NZ - JACK

#### Emergency telephone number

Association / Organisation	CRC Industries (CRC Industries New Zealand)
Emergency telephone numbers	NZ Poisons Centre 0800 POISON (0800 764 766)
Other emergency telephone numbers	111 (NZ Emergency Services)

### SECTION 2 Hazards identification

#### Classification of the substance or mixture

Considered a Hazardous Substance according to the criteria of the New Zealand Hazardous Substances New Organisms legislation.  
Classified as Dangerous Goods for transport purposes.

#### Chemwatch Hazard Ratings

	Min	Max
Flammability	3	
Toxicity	1	
Body Contact	1	
Reactivity	1	
Chronic	0	

0 = Minimum  
1 = Low  
2 = Moderate  
3 = High  
4 = Extreme

#### Classification [1]

Aerosols Category 1, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Hazardous to the Aquatic Environment Long-Term Hazard Category 2

<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
<b>Determined by Chemwatch using GHS/HSNO criteria</b>	2.1.2A, 6.9B (narcotic effects), 9.1B

## Label elements

<b>Hazard pictogram(s)</b>	
<b>Signal word</b>	<b>Danger</b>

## Hazard statement(s)

<b>H222+H229</b>	Extremely flammable aerosol. Pressurized container: may burst if heated.
<b>H336</b>	May cause drowsiness or dizziness.
<b>H411</b>	Toxic to aquatic life with long lasting effects.

## Precautionary statement(s) Prevention

<b>P210</b>	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
<b>P211</b>	Do not spray on an open flame or other ignition source.
<b>P251</b>	Do not pierce or burn, even after use.
<b>P271</b>	Use only outdoors or in a well-ventilated area.
<b>P261</b>	Avoid breathing mist/vapours/spray.
<b>P273</b>	Avoid release to the environment.

## Precautionary statement(s) Response

<b>P312</b>	Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.
<b>P391</b>	Collect spillage.
<b>P304+P340</b>	IF INHALED: Remove person to fresh air and keep comfortable for breathing.

## Precautionary statement(s) Storage

<b>P405</b>	Store locked up.
<b>P410+P412</b>	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
<b>P403+P233</b>	Store in a well-ventilated place. Keep container tightly closed.

## Precautionary statement(s) Disposal

<b>P501</b>	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
-------------	--

## SECTION 3 Composition / information on ingredients

### Substances

See section below for composition of Mixtures

### Mixtures

CAS No	%[weight]	Name
107-83-5	<5	<u>2-methylpentane</u>
1314-13-2	2-5	<u>zinc oxide</u>
Not Available	25-35	grease
68476-86-8.	20-40	<u>hydrocarbon propellant</u>

**Legend:** 1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; \* EU IOELVs available

## SECTION 4 First aid measures

### Description of first aid measures

<b>Eye Contact</b>	<p>If aerosols come in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold the eyelids apart and flush the eye with fresh running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If solids or aerosol mists are deposited upon the skin:</p> <ul style="list-style-type: none"> <li>▶ Flush skin and hair with running water (and soap if available).</li> <li>▶ Remove any adhering solids with industrial skin cleansing cream.</li> <li>▶ <b>DO NOT use solvents.</b></li> <li>▶ Seek medical attention in the event of irritation.</li> </ul>
<b>Inhalation</b>	<p>If aerosols, fumes or combustion products are inhaled:</p> <ul style="list-style-type: none"> <li>▶ Remove to fresh air.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ If breathing is shallow or has stopped, ensure clear airway and apply resuscitation, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> <li>▶ Not considered a normal route of entry.</li> </ul>

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5 Firefighting measures

### Extinguishing media

- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

**Do not** use water jets.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Advice for firefighters

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ If safe, switch off electrical equipment until vapour fire hazard removed.</li> <li>▶ Use water delivered as a fine spray to control fire and cool adjacent area.</li> <li>▶ <b>DO NOT</b> approach containers suspected to be hot.</li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> <li>▶ If safe to do so, remove containers from path of fire.</li> <li>▶ Equipment should be thoroughly decontaminated after use.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat or flame.</li> <li>▶ Vapour forms an explosive mixture with air.</li> <li>▶ Severe explosion hazard, in the form of vapour, when exposed to flame or spark.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition with violent container rupture.</li> <li>▶ Aerosol cans may explode on exposure to naked flames.</li> <li>▶ Rupturing containers may rocket and scatter burning materials.</li> <li>▶ Hazards may not be restricted to pressure effects.</li> <li>▶ May emit acrid, poisonous or corrosive fumes.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> </ul> <p>Combustion products include:  carbon monoxide (CO)  carbon dioxide (CO<sub>2</sub>)  other pyrolysis products typical of burning organic material.</p> <p><b>Contains low boiling substance:</b> Closed containers may rupture due to pressure buildup under fire conditions.</p>

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**Environmental precautions**

See section 12

**Methods and material for containment and cleaning up**

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Wear protective clothing, impervious gloves and safety glasses.</li> <li>▶ Shut off all possible sources of ignition and increase ventilation.</li> <li>▶ Wipe up.</li> <li>▶ If safe, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.</li> <li>▶ Undamaged cans should be gathered and stowed safely.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ May be violently or explosively reactive.</li> <li>▶ Wear breathing apparatus plus protective gloves.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water courses</li> <li>▶ No smoking, naked lights or ignition sources.</li> <li>▶ Increase ventilation.</li> <li>▶ Stop leak if safe to do so.</li> <li>▶ Water spray or fog may be used to disperse / absorb vapour.</li> <li>▶ Absorb or cover spill with sand, earth, inert materials or vermiculite.</li> <li>▶ If safe, damaged cans should be placed in a container outdoors, away from ignition sources, until pressure has dissipated.</li> <li>▶ Undamaged cans should be gathered and stowed safely.</li> <li>▶ Collect residues and seal in labelled drums for disposal.</li> </ul>


Personal Protective Equipment advice is contained in Section 8 of the SDS.

**SECTION 7 Handling and storage****Precautions for safe handling**

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li> <li>▶ Avoid smoking, naked lights or ignition sources.</li> <li>▶ Avoid contact with incompatible materials.</li> <li>▶ <b>When handling, DO NOT eat, drink or smoke.</b></li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> <li>▶ <b>DO NOT spray directly on humans, exposed food or food utensils.</b></li> <li>▶ Avoid physical damage to containers.</li> <li>▶ Always wash hands with soap and water after handling.</li> <li>▶ Work clothes should be laundered separately.</li> <li>▶ Use good occupational work practice.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> <li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions are maintained.</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store below 38 deg. C.</li> <li>▶ Keep dry to avoid corrosion of cans. Corrosion may result in container perforation and internal pressure may eject contents of can</li> <li>▶ Store in original containers in approved flammable liquid storage area.</li> <li>▶ <b>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</b></li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ Keep containers securely sealed. Contents under pressure.</li> <li>▶ Store away from incompatible materials.</li> <li>▶ Store in a cool, dry, well ventilated area.</li> <li>▶ Avoid storage at temperatures higher than 40 deg C.</li> <li>▶ Store in an upright position.</li> <li>▶ Protect containers against physical damage.</li> <li>▶ Check regularly for spills and leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Aerosol dispenser.</li> <li>▶ Check that containers are clearly labelled.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid reaction with oxidising agents</li> </ul> <p>44acidbase</p>



X — Must not be stored together

O — May be stored together with specific preventions

+ — May be stored together

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

## SECTION 8 Exposure controls / personal protection

### Control parameters

#### Occupational Exposure Limits (OEL)

#### INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide	2 mg/m <sup>3</sup>	5 mg/m <sup>3</sup>	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	zinc oxide	Zinc oxide respirable dust	0.1 mg/m <sup>3</sup>	0.5 mg/m <sup>3</sup>	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	hydrocarbon propellant	LPG (Liquefied petroleum gas)	1000 ppm / 1800 mg/m <sup>3</sup>	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
2-methylpentane	Not Available	Not Available
zinc oxide	500 mg/m <sup>3</sup>	Not Available
hydrocarbon propellant	Not Available	Not Available


#### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
2-methylpentane	E	≤ 0.1 ppm
<b>Notes:</b>	<i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i>	

#### MATERIAL DATA

### Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.  General exhaust is adequate under normal conditions. If risk of overexposure exists, wear SAA approved respirator. Correct fit is essential to obtain adequate protection. Provide adequate ventilation in warehouse or closed storage areas. Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.								
	<table border="1"> <thead> <tr> <th>Type of Contaminant:</th> <th>Speed:</th> </tr> </thead> <tbody> <tr> <td>aerosols, (released at low velocity into zone of active generation)</td> <td>0.5-1 m/s</td> </tr> <tr> <td>direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)</td> <td>1-2.5 m/s (200-500 f/min.)</td> </tr> </tbody> </table>	Type of Contaminant:	Speed:	aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s	direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)		
Type of Contaminant:	Speed:								
aerosols, (released at low velocity into zone of active generation)	0.5-1 m/s								
direct spray, spray painting in shallow booths, gas discharge (active generation into zone of rapid air motion)	1-2.5 m/s (200-500 f/min.)								
	<p>Within each range the appropriate value depends on:</p> <table border="1"> <thead> <tr> <th>Lower end of the range</th> <th>Upper end of the range</th> </tr> </thead> <tbody> <tr> <td>1: Room air currents minimal or favourable to capture</td> <td>1: Disturbing room air currents</td> </tr> <tr> <td>2: Contaminants of low toxicity or of nuisance value only.</td> <td>2: Contaminants of high toxicity</td> </tr> <tr> <td>3: Intermittent, low production.</td> <td>3: High production, heavy use</td> </tr> </tbody> </table>	Lower end of the range	Upper end of the range	1: Room air currents minimal or favourable to capture	1: Disturbing room air currents	2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity	3: Intermittent, low production.	3: High production, heavy use
Lower end of the range	Upper end of the range								
1: Room air currents minimal or favourable to capture	1: Disturbing room air currents								
2: Contaminants of low toxicity or of nuisance value only.	2: Contaminants of high toxicity								
3: Intermittent, low production.	3: High production, heavy use								

	4: Large hood or large air mass in motion	4: Small hood-local control only
	Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.	
<b>Individual protection measures, such as personal protective equipment</b>		
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ No special equipment for minor exposure i.e. when handling small quantities.</li> <li>▶ OTHERWISE: For potentially moderate or heavy exposures: <ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> </ul> </li> <li>▶ NOTE: Contact lenses pose a special hazard; soft lenses may absorb irritants and ALL lenses concentrate them.</li> </ul>	
<b>Skin protection</b>	See Hand protection below	
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ No special equipment needed when handling small quantities.</li> <li>▶ OTHERWISE: <ul style="list-style-type: none"> <li>▶ For potentially moderate exposures: <ul style="list-style-type: none"> <li>▶ Wear general protective gloves, eg. light weight rubber gloves.</li> <li>▶ For potentially heavy exposures: <ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, eg. PVC. and safety footwear.</li> </ul> </li> </ul> </li> </ul> </li> </ul>	
<b>Body protection</b>	See Other protection below	
<b>Other protection</b>	<p>No special equipment needed when handling small quantities.</p> <p><b>OTHERWISE:</b></p> <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ Skin cleansing cream.</li> <li>▶ Eyewash unit.</li> <li>▶ Do not spray on hot surfaces.</li> <li>▶ The clothing worn by process operators insulated from earth may develop static charges far higher (up to 100 times) than the minimum ignition energies for various flammable gas-air mixtures. This holds true for a wide range of clothing materials including cotton.</li> <li>▶ Avoid dangerous levels of charge by ensuring a low resistivity of the surface material worn outermost.</li> </ul> <p>BREThERICK: Handbook of Reactive Chemical Hazards.</p>	

## Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	AX-AUS	-	AX-PAPR-AUS / Class 1
up to 50 x ES	-	AX-AUS / Class 1	-
up to 100 x ES	-	AX-2	AX-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	White highly flammable liquid with lubricant/ solvent odour; does not mix with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.68
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available

<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Applicable	<b>Decomposition temperature (°C)</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	Not Available	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	<10	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	Not Available	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	Not Available	<b>Volatile Component (%vol)</b>	Not Available
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Immiscible	<b>pH as a solution (1%)</b>	Not Applicable
<b>Vapour density (Air = 1)</b>	Not Available	<b>VOC g/L</b>	Not Available
<b>Heat of Combustion (kJ/g)</b>	Not Available	<b>Ignition Distance (cm)</b>	Not Available
<b>Flame Height (cm)</b>	Not Available	<b>Flame Duration (s)</b>	Not Available
<b>Enclosed Space Ignition Time Equivalent (s/m3)</b>	Not Available	<b>Enclosed Space Ignition Deflagration Density (g/m3)</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Elevated temperatures.</li> <li>▶ Presence of open flame.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

### Information on toxicological effects

<b>Inhaled</b>	<p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.</p> <p>Limited evidence or practical experience suggests that the material may produce irritation of the respiratory system, in a significant number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Acute effects from inhalation of high concentrations of vapour are pulmonary irritation, including coughing, with nausea; central nervous system depression - characterised by headache and dizziness, increased reaction time, fatigue and loss of co-ordination. Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p><b>WARNING: Intentional misuse by concentrating/inhaling contents may be lethal.</b></p>
<b>Ingestion</b>	<p>Accidental ingestion of the material may be damaging to the health of the individual.</p> <p>Considered an unlikely route of entry in commercial/industrial environments</p>
<b>Skin Contact</b>	<p>Repeated exposure may cause skin cracking, flaking or drying following normal handling and use.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>
<b>Eye</b>	<p>Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn).</p>

<b>Chronic</b>	Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems. <b>WARNING: Aerosol containers may present pressure related hazards.</b>	
<b>CRC Food Grade White Grease (Fg03038)</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>2-methylpentane</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Oral (Rat) LD50: ~15.84 mg/kg <sup>[1]</sup>	Not Available
<b>zinc oxide</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	dermal (rat) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit) : 500 mg/24 h - mild
	Inhalation (Rat) LC50: >1.79 mg/l4h <sup>[1]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
	Oral (Rat) LD50: >5000 mg/kg <sup>[1]</sup>	Skin (rabbit) : 500 mg/24 h- mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
<b>hydrocarbon propellant</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Inhalation (Rat) LC50: 658 mg/l4h <sup>[2]</sup>	Not Available
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

<b>ZINC OXIDE</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.
<b>HYDROCARBON PROPELLANT</b>	<p>for Petroleum Hydrocarbon Gases:</p> <p>In many cases, there is more than one potentially toxic constituent in a refinery gas. In those cases, the constituent that is most toxic for a particular endpoint in an individual refinery stream is used to characterize the endpoint hazard for that stream. The hazard potential for each mammalian endpoint for each of the petroleum hydrocarbon gases is dependent upon each petroleum hydrocarbon gas constituent endpoint toxicity values (LC50, LOAEL, etc.) and the relative concentration of the constituent present in that gas. It should also be noted that for an individual petroleum hydrocarbon gas, the constituent characterizing toxicity may be different for different mammalian endpoints, again, being dependent upon the concentration of the different constituents in each, distinct petroleum hydrocarbon gas.</p> <p>All Hydrocarbon Gases Category members contain primarily hydrocarbons (i.e., alkanes and alkenes) and occasionally asphyxiant gases like hydrogen. The inorganic components of the petroleum hydrocarbon gases are less toxic than the C1 - C4 and C5 - C6 hydrocarbon components to both mammalian and aquatic organisms. Unlike other petroleum product categories (e.g. gasoline, diesel fuel, lubricating oils, etc.), the inorganic and hydrocarbon constituents of hydrocarbon gases can be evaluated for hazard individually to then predict the screening level hazard of the Category members</p> <p><b>Acute toxicity:</b> No acute toxicity LC50 values have been derived for the C1 -C4 and C5- C6 hydrocarbon (HC) fractions because no mortality was observed at the highest exposure levels tested (~ 5 mg/l) for these petroleum hydrocarbon gas constituents. The order of acute toxicity of petroleum hydrocarbon gas constituents from most to least toxic is: C5-C6 HCs (LC50 &gt; 1063 ppm) &gt; C1-C4 HCs (LC50 &gt; 10,000 ppm) &gt; benzene (LC50 = 13,700 ppm) &gt; butadiene (LC50 = 129,000 ppm) &gt; asphyxiant gases (hydrogen, carbon dioxide, nitrogen).</p> <p><b>Repeat dose toxicity:</b> With the exception of the asphyxiant gases, repeated dose toxicity has been observed in individual selected petroleum hydrocarbon gas constituents. Based upon LOAEL values, the order of order of repeated-dose toxicity of these constituents from most toxic to the least toxic is: Benzene (LOAEL .&gt;=10 ppm) &gt;C1-C4 HCs (LOAEL = 5,000 ppm; assumed to be 100% 2-butene) &gt; C5-C6 HCs (LOAEL = 6,625 ppm) &gt; butadiene (LOAEL = 8,000 ppm) &gt; asphyxiant gases (hydrogen, carbon dioxide, nitrogen).</p> <p><b>Genotoxicity:</b></p> <p><b>In vitro:</b> The majority of the Petroleum Hydrocarbon Gases Category components are negative for <i>in vitro</i> genotoxicity. The exceptions are: benzene and 1,3-butadiene, which are genotoxic in bacterial and mammalian <i>in vitro</i> test systems.</p> <p><b>In vivo:</b> The majority of the Petroleum Hydrocarbon Gases Category components are negative for <i>in vivo</i> genotoxicity. The exceptions are benzene and 1,3-butadiene, which are genotoxic in <i>in vivo</i> test systems</p> <p><b>Developmental toxicity:</b> Developmental effects were induced by two of the petroleum hydrocarbon gas constituents, benzene and the C5 -C6 hydrocarbon fraction. No developmental toxicity was observed at the highest exposure levels tested for the other petroleum hydrocarbon gas constituents tested for this effect. The asphyxiant gases have not been tested for developmental toxicity. Based on LOAEL and NOAEL values, the order of acute toxicity of these constituents from most to least toxic is: Benzene (LOAEL = 20 ppm) &gt; butadiene (NOAEL .&gt;=1,000 ppm) &gt; C5-C6 HCs (LOAEL = 3,463 ppm) &gt; C1-C4 HCs (NOAEL .&gt;=5,000 ppm; assumed to be 100% 2-butene) &gt; asphyxiant gases (hydrogen, carbon dioxide, nitrogen).</p> <p><b>Reproductive toxicity:</b> Reproductive effects were induced by only two petroleum hydrocarbon gas constituents, benzene and isobutane (a constituent of the the C1-C4 hydrocarbon fraction). No reproductive toxicity was observed at the highest exposure levels tested for the other petroleum hydrocarbon gas constituents tested for this effect. The asphyxiant gases have not been tested for reproductive toxicity. Based on LOAEL and NOAEL values, the order of reproductive toxicity of these constituents from most to least toxic is: Benzene (LOAEL = 300 ppm) &gt; butadiene (NOAEL .&gt;=6,000 ppm) &gt; C5-C6 HCs (NOAEL .&gt;=6,521 ppm) &gt; C1-C4 HCs (LOAEL = 9,000 ppm; assumed to be 100% isobutane) &gt; asphyxiant gases (hydrogen, carbon dioxide, nitrogen)</p>
<b>2-METHYLPENTANE &amp; HYDROCARBON</b>	No significant acute toxicological data identified in literature search.

**PROPELLANT**

Acute Toxicity	✗	Carcinogenicity	✗
Skin Irritation/Corrosion	✗	Reproductivity	✗
Serious Eye Damage/Irritation	✗	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✗	STOT - Repeated Exposure	✗
Mutagenicity	✗	Aspiration Hazard	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

**SECTION 12 Ecological information**

**Toxicity**

	Endpoint	Test Duration (hr)	Species	Value	Source
CRC Food Grade White Grease (Fg03038)	Not Available	Not Available	Not Available	Not Available	Not Available
2-methylpentane	EC50(ECx)	96h	Algae or other aquatic plants	4.321mg/l	2
	EC50	96h	Algae or other aquatic plants	4.321mg/l	2
zinc oxide	BCF	1344h	Fish	19-110	7
	EC50	72h	Algae or other aquatic plants	0.022mg/L	2
	ErC50	72h	Algae or other aquatic plants	0.62mg/l	2
	EC50	48h	Crustacea	0.105mg/L	2
	LC50	96h	Fish	0.102mg/L	2
	EC10(ECx)	168h	Algae or other aquatic plants	0.003mg/L	2
	EC50	96h	Algae or other aquatic plants	0.042mg/L	2
hydrocarbon propellant	LC50	96h	Fish	24.11mg/l	2
	EC50(ECx)	96h	Algae or other aquatic plants	7.71mg/l	2
	EC50	96h	Algae or other aquatic plants	7.71mg/l	2

**Legend:** *Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data*

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

**DO NOT discharge into sewer or waterways.**

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
2-methylpentane	LOW	LOW

**Bioaccumulative potential**

Ingredient	Bioaccumulation
2-methylpentane	LOW (LogKOW = 3.2145)
zinc oxide	LOW (BCF = 217)

**Mobility in soil**

Ingredient	Mobility
2-methylpentane	LOW (Log KOC = 124.9)

**SECTION 13 Disposal considerations**

## Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Consult State Land Waste Management Authority for disposal.</li> <li>▶ Discharge contents of damaged aerosol cans at an approved site.</li> <li>▶ Allow small quantities to evaporate.</li> <li>▶ <b>DO NOT incinerate or puncture aerosol cans.</b></li> <li>▶ Bury residues and emptied aerosol cans at an approved site.</li> </ul>
-------------------------------------	---

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

## Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

DO NOT deposit the hazardous substance into or onto a landfill or a sewage facility.

Burning the hazardous substance must happen under controlled conditions with no person or place exposed to



(1) a blast overpressure of more than 9 kPa; or

(2) an unsafe level of heat radiation.

The disposed hazardous substance must not come into contact with class 1 or 5 substances.

## SECTION 14 Transport information

### Labels Required

	
Marine Pollutant	
HAZCHEM	Not Applicable

### Land transport (UN)

14.1. UN number or ID number	1950	
14.2. UN proper shipping name	AEROSOLS	
14.3. Transport hazard class(es)	Class	2.1
	Subsidiary Hazard	Not Applicable
14.4. Packing group	Not Applicable	
14.5. Environmental hazard	Environmentally hazardous	
14.6. Special precautions for user	Special provisions	63; 190; 277; 327; 344; 381
	Limited quantity	1000ml

### Air transport (ICAO-IATA / DGR)

14.1. UN number	1950	
14.2. UN proper shipping name	Aerosols, flammable	
14.3. Transport hazard class(es)	ICAO/IATA Class	2.1
	ICAO / IATA Subsidiary Hazard	Not Applicable
	ERG Code	10L
14.4. Packing group	Not Applicable	
	Environmentally hazardous	

<b>14.5. Environmental hazard</b>		
<b>14.6. Special precautions for user</b>	Special provisions	A145 A167 A802
	Cargo Only Packing Instructions	203
	Cargo Only Maximum Qty / Pack	150 kg
	Passenger and Cargo Packing Instructions	203
	Passenger and Cargo Maximum Qty / Pack	75 kg
	Passenger and Cargo Limited Quantity Packing Instructions	Y203
	Passenger and Cargo Limited Maximum Qty / Pack	30 kg G

### Sea transport (IMDG-Code / GGVSee)

<b>14.1. UN number</b>	1950	
<b>14.2. UN proper shipping name</b>	AEROSOLS	
<b>14.3. Transport hazard class(es)</b>	IMDG Class	2.1
	IMDG Subsidiary Hazard	Not Applicable
<b>14.4. Packing group</b>	Not Applicable	
<b>14.5. Environmental hazard</b>	Marine Pollutant	
<b>14.6. Special precautions for user</b>	EMS Number	F-D , S-U
	Special provisions	63 190 277 327 344 381 959
	Limited Quantities	1000 ml

#### 14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### 14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2-methylpentane	Not Available
zinc oxide	Not Available
hydrocarbon propellant	Not Available

#### 14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
2-methylpentane	Not Available
zinc oxide	Not Available
hydrocarbon propellant	Not Available

## SECTION 15 Regulatory information

### Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002515	Aerosols (Flammable) Group Standard 2017

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

#### 2-methylpentane is found on the following regulatory lists

- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data
- New Zealand Inventory of Chemicals (NZIoC)

#### zinc oxide is found on the following regulatory lists

- International WHO List of Proposed Occupational Exposure Limit (OEL) Values for Manufactured Nanomaterials (MNMS)
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals
- New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Land Transport Rule: Dangerous Goods 2005 - Schedule 1 Quantity limits for dangerous goods

New Zealand Workplace Exposure Standards (WES)

#### hydrocarbon propellant is found on the following regulatory lists

Chemical Footprint Project - Chemicals of High Concern List

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

#### Additional Regulatory Information

Not Applicable

#### Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Closed Containers)	Quantity (Open Containers)
2.1.2A	3 000 L (aggregate water capacity)	3 000 L (aggregate water capacity)

#### Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

#### Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
2.1.2A				1L (aggregate water capacity)

#### Tracking Requirements

Not Applicable

#### National Inventory Status

National Inventory	Status
Australia - AIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (2-methylpentane; hydrocarbon propellant)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - FBEPH	Yes
<b>Legend:</b>	<i>Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.</i>

#### SECTION 16 Other information

<b>Revision Date</b>	10/12/2021
<b>Initial Date</b>	06/08/2008

## SDS Version Summary

Version	Date of Update	Sections Updated
6.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
7.1	10/12/2021	Classification change due to full database hazard calculation/update.

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

## Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
  
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.



**CRC Food Grade White Grease** is a high purity, high quality synthetic grease with an advanced additive package that provides superior lubrication, durability, corrosion protection, film strength and excellent water and heat resistance.

Convenient aerosol application allows for lubricating hard-to-reach areas. This versatile grease is designed for high load applications requiring a long grease life and is ideal for heavy-duty metal-to-metal lubrication.

Wide temperature range from -17°C to +230°C. MPI Approved. NSF H1 Registered for incidental food contact.

**Item Code: 3038    Pack Size: 284g Aerosol**

## Features and Benefits

- **Excellent adhesion:** Resists throw-off and wash-out, forms an effective corrosion barrier
- **Aerosol:** Easy application, ideal for hard-to-reach areas, no clean-up. Can be build up with several layers for improved waterproofing
- **White Coloration:** Easy visual film check
- **360° valve:** Aerosol can be sprayed from any position even upside down
- **Non-toxic, mild odour, tasteless**
- **Wide Temperature range:** Effective from -17°C to +230°C
- **MPI Approved C15** for all animal product except dairy
- **MPI Approved** for use at farm dairies and in dairy processing
- **NSF H1 Registered for incidental food contact**

## Typical Properties and Characteristics

Flash Point	<0°C (Propellant)
Odour	Slight odour
Appearance	Off white grease
Solubility	Negligible in water
NLGI Grade	2
Vapour Density	> Air
Specific Gravity	0.90
Propellant	Hydrocarbon

Drop Point (ASTM D-2268)	250°C
Timken OK Load (ASTM D-2268)	30 lbs
Viscosity-Base Oil @ 100°F	SUS 600
Viscosity-Base Oil @ 210°F	SUS 69
Four Ball EP Weld (ASTM D-2596)	400 kg F
Temperature range	-17°C to +230°C

## Directions

1. Do not apply while equipment is energized.
2. Shake well before use.
3. Spray in light and even coats.
4. Use extension tube for hard-to-reach areas.

## Special Precautions

### General:

Extremely flammable aerosol. Keep away from naked flames, electrical appliances/lights, lighted cigarettes, etc. Do not spray on open flame or other ignition source. Use with adequate ventilation. Store in a cool, well-ventilated area. Do not eat, drink or smoke when using this product. Dispose of contents/container in accordance with relevant regulations. All unused product should be disposed of in conformance with local and hazard regulations, do not contaminate water supply.

### Aerosol Cans:

Do not puncture, incinerate or store above 50°C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

Refer to **Safety Data Sheet** for more details.

## Product Warranty or Shelf Life

CRC offers a conditional warranty on this product for the period of 5 years from the date of manufacture.

## Contact Information

**CRC Industries NZ**  
10 Highbrook Dr, East Tamaki  
Auckland, New Zealand

**www.crc.co.nz**  
PH: 09 272 2700  
Email: info.nz@crcind.com

**Disclaimer:** All information on this data sheet is based on testing by CRC Industries NZ. All products should be tested for suitability on a particular application prior to actual use. CRC Industries NZ makes no representations or warranties of any kind concerning this data.

*Technical Data Sheet Version 10/2024*

12 July 2024

Natasha Gill  
CRC Industries New Zealand  
PO Box 204267  
Highbrook  
Manukau 2161

Dear Natasha,

## APPROVAL OF DAIRY MAINTENANCE COMPOUND FOR USE IN FARM DAIRIES AND FOR USE IN DAIRY PROCESSING

The new product **Food Grade White Grease** has been considered in conjunction with the type of validation information provided and has been determined to satisfy the requirements of regulations 12, 13, 14, 53 and 247 of the Animal Products Regulations 2021 and regulation 43 of the Raw Milk for Sale Consumers Regulations 2015, when used in accordance with the label.

The product **Food Grade White Grease** has been assessed and is approved for use in farm dairies and for use in dairy premises when used in accordance with label instructions.

This approval of the compound for use in farm dairies and dairy processing is subject to the following conditions:

1. To be used in accordance with label instructions as a lubricant.
2. Not to be used on food contact surfaces.
3. The method of use must ensure that milk, food, packaging or food contact surfaces will not be adversely affected.
4. Only sufficient lubricant to achieve the required effect is to be used.
5. Should incidental contact with food contact surfaces occur, surfaces must be cleaned and thoroughly rinsed to ensure no residue remains.


Where this approval is stated on the product label, the statement "MPI approved for use in farm dairies" and "MPI approved for use in dairy processing" is to be used, unless an alternative is agreed in writing by MPI.

Should this product be determined to be unsatisfactory when used as recommended by the manufacturer or an agent of the manufacturer at the stated dosage, MPI may withdraw this approval.

### Review

This approval of a dairy maintenance compound for use in farm dairies and dairy processing is valid for a maximum period of 5 years but is subject to periodic review and may be withdrawn at any time should the Director-General determine that there is sufficient evidence that the product is not fit for the purpose for which this approval applies. You will be issued a letter prior to the review date, which is set at **12 July 2029**, but you are responsible for ensuring that this review is completed if you wish to retain MPI approval of the above dairy maintenance compound.

Yours faithfully,



Shaleen Narayan  
Manager Approvals  
Acting under delegated authority  
Ministry for Primary Industries

19 March 2024

CRC Industries New Zealand  
PO Box 204267  
Highbrook  
Manukau 2161

**Trade Name:** Food Grade White Grease  
**Description:** Lubricant  
**Code:** C 15

## Approvals:

This compound is approved for use in premises processing all animal product except dairy, operating under the Animal Products Act regime.

This approval is under the following regulations, subject to the conditions stated in this approval:

1. Regulation 247 of the Animal Products Regulations 2021 and Regulation 18 of the Animal Products (Regulated Control Scheme – Limited Processing Fishing Vessels) Regulations 2001

## Conditions:

1. This is permitted to be used during processing of food to lubricate moving parts of equipment whereby the lubricated surface is either an integral part of the food contact surface, or is contiguous with the food contact surface and contamination could result from bearing seal leakage.
2. The equipment is to be maintained, including the application of lubricants, according to the specifications of the equipment manufacturer.
3. Only sufficient lubricant is to be used to achieve the desired effect.
4. When used in the manner permitted, all lubricated surfaces are to be maintained according to requirements for sanitation of food contact surfaces.
5. When used in any other manner that may result in incidental contamination of a food surface, the surface is to be cleaned by washing to ensure no free substance remains that could be transferred to food being processed.

This approval may be withdrawn at any time due to unapproved directions for use, or unsatisfactory performance, or any change in product formulation. The Ministry for Primary Industries (New Zealand Food Safety) must be notified if the holder of this approval wishes to transfer their products to another entity.

The product must be used in accordance with the manufacturer's instructions and specifications. The label may include a statement to the effect that the product is approved for use in premises registered under the Animal Products Act regime. Any statements made, however, must include the approval code and must be limited to the following unless otherwise specified:

MPI Approved C 15 (All animal product except dairy)

Note: Former NZFSA statements must be removed from your labels.

**This approval must not be used as a Ministry for Primary Industries (MPI) endorsement of any claim made for the product by the manufacturer.**

This approval will remain valid until 19 March 2029 unless the approval is revoked by notice in writing at an earlier stage.

Any queries regarding this approval should be directed to MPI Approvals by either telephone on 04 894 2550 or by e-mail at [approvals@mpi.govt.nz](mailto:approvals@mpi.govt.nz).

Yours sincerely,



Shaleen Narayan  
Manager Approvals  
Regulatory Systems & Support

---

**Ministry for Primary Industries**  
Manatū Ahu Matua

---



Date: 19 March 2024

**Official Receipt G.S.T. 64-558-838**

Received from: **CRC Industries New Zealand**

Maintenance compound approval fee for: **Food Grade White Grease**

Sum of: **\$77.63**

---



# CRC Industries, Inc.

Global Headquarters: 800 Enterprise Road, Suite 101 | Horsham, PA 19044 | 215.674.4300

Manufacturing and R&D Center: 885 Louis Drive | Warminster, PA 18974 | 215.674.4300

## ALLERGEN CERTIFICATE

**Date:** 21-Feb-23

**Product Name:** Food Grade White Grease

**Product Code:** No. 03038 (Item# 1003292)

CRC has evaluated the above product against a list of internationally recognized and regulated allergens. The following information is provided to assist our customers in complying with allergen safety programs.

Allergen	Present in Product	Present on Same Production Line	Present in Facility
Dairy / Milk	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Soy	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Peanut	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Egg	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Tree Nut (almonds, brazil nuts, cashews, hazelnuts, macadamia nuts, pecans, pine nuts, pistachio nuts and walnuts)	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Sesame Seed	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Mustard Seed	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Gluten (wheat, barley, oats, rye)	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Seafood (fish, crustacean and molluscan shellfish)	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Sulfites	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Buckwheat	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Celery	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Lupin	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Bee pollen / Propolis	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Royal Jelly	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Mango	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Peach	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Pork	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Tomato	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No
Latex (natural rubber)	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No	<input type="checkbox"/> Yes / <input checked="" type="checkbox"/> No

This information is accurate to the best of CRC Industries' knowledge or obtained from sources believed by CRC to be accurate. For more information, please contact our Technical Service Dept at 800-521-3168.

CRC INDUSTRIES, INC.

*Michelle Rudnick*

Michelle Rudnick  
Global Director of Regulatory Affairs



March 30, 2022

CRC Industries (Aust.) Pty Limited  
9 Gladstone Road  
Castle Hill, NSW 2154  
Australia

**RE:** CRC Food Grade White Grease Aerosol  
Category Code: H1  
NSF Registration No. 165945

NSF has processed the application for Registration of **CRC Food Grade White Grease Aerosol** to the *NSF International Registration Guidelines for Proprietary Substances and Nonfood Compounds* (2021), which are available upon request by contacting [NonFood@nsf.org](mailto:NonFood@nsf.org). The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling review.

**This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.**

NSF Registration of this product is current when the NSF Registration Mark and Category Code appear on the NSF-approved product label, and the Registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website ([www.nsfwhitebook.org](http://www.nsfwhitebook.org)).

NSF Listing of all Registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF website, at [www.nsfwhitebook.org](http://www.nsfwhitebook.org). Please note the letter date reflects most recent product review. NSF utilizes annual verification to ensure no changes have been made to a registered product. Changes in formulation or label, without the prior written consent of NSF, will void Registration, and will supersede the on-line listing. Please contact your NSF Account Manager or [nonfood@nsf.org](mailto:nonfood@nsf.org) if you have any questions or concerns pertaining to this letter.

Sincerely,

Orsolya Dezsi  
NSF NonFood Compound Registration Program  
Company No: 1D690